

Quantity Guide Protector & Slimline Dock Fenders

PROTECTOR FENDERS

Diameters 350 mm / 450 mm. Step and Repeat distances 600 mm between end D - Rings.

SLIMLINE FENDERS

Sizes 200 mm x 300 mm .Step and Repeat distances 500 mm between end D - Rings.

m	DOCK SIDE - Protector Fenders: 1m / 1.5m / 3.0m / 6.0m	STERN	m	DOCK SIDE - Slimline Fenders: 1m / 1.5m / 3.0m	STERN
10	1 x 1000 mm (corner) / 1 x 1500 mm + 2 x 3000 mm	1 x 3000 mm	10	1 x 1000 mm (corner) / 1 x 1500 mm + 2 x 3000 mm	1 x 3000 mm
12	1 x 1000 mm (corner) / 1 x 1500 mm + 3 x 3000 mm	1 x 3000 mm	12	1 x 1000 mm (corner) / 1 x 1500 mm + 3 x 3000 mm	1 x 3000 mm
14	1 x 1000 mm (corner) / 1 x 1500 mm + 3 x 3000 mm	1 x 3000 mm	14	1 x 1000 mm (corner) / 1 x 1500 mm + 3 x 3000 mm	1 x 3000 mm
	1 x 1000 mm (corner) / 1 x 1500 mm + 1 x 3000 mm + 1 x 6000 mm	1 x 3000 mm			
16	1 x 1000 mm (corner) / 1 x 1500 mm / 3 x 3000 mm	1 x 3000 mm / 1 x 1500 mm			
	1 x 1000 mm (corner) / 1 x 1500 mm / 2 x 6000 mm	1 x 3000 mm / 1 x 1500 mm			
18	1 x 1500 mm (corner) / 5 x 3000 mm	2 x 3000 mm			
	1 x 1500 mm (corner) / 1 x 3000 mm / 2 x 6000 mm	1 x 6000 mm			
20	1 x 1500 mm (corner) / 6 x 3000 mm	2 x 3000 mm			
	1 x 1500 mm (corner) / 3 x 6000 mm	1 x 6000 mm			

NOTE: The above quantities are estimates only. Please check your dock, berth or slip before ordering to ensure the correct quantities. Fenders are designed to press against the side of the dock. (clear of the water). Generally 200 mm wide wooden siding.